

# MILLIKEN MOISTURE PRO 95

## Material Safety Data Sheet

Moisture Pro 95 is only available within the USA.

### MANUFACTURER'S NAME

XL Brands  
198 Nexus Drive  
Dalton, GA 30721  
1-800-367-4583

### 24-HOUR EMERGENCY

Chemtrec 1-800-424-9300

### PRODUCT IDENTIFICATION

Product Class: Aqueous Polymer Aerosol Spray Adhesive  
Product Name: Stix Essential MOD

### HAZARDOUS INGREDIENTS

None known

\*All components of this product appear on the Inventory of Chemical Substances published by the U.S. Environmental Protection Agency (EPA) under the authority of the Toxic Substances Control Act (TSCA).

### PHYSICAL DATA

Boiling Point: 212° F  
Vapor Density: Same as water  
Evaporation Rate: Same as water  
Appearance: White, creamy  
Odor: Low odor  
Weight per Gallon: 8.2 lbs. typical  
Solubility in Water: Not soluble (dispersible)  
VOC (grams per liter): Zero calculated

### FIRE AND EXPLOSION HAZARD DATA

Contains gas under pressure. Container may explode if heated.  
Flammable Limits: Non-flammable  
Flash Point: > 212° F  
Flammability Classification: None  
Extinguishing Media: CO<sub>2</sub>, chemical foam, water fog

### SPECIAL FIRE FIGHTING FEATURES

Wear self-contained breathing gear when in confined area

### HEALTH HAZARD DATA

Threshold Limit Value: Not established  
Effects of Overexposure: No known chronic overexposure effects

### EMERGENCY AND FIRST AID PROCEDURE

Eye Contact: May cause irritation.  
In case of eye contact, flush with water for 10–15 minutes. If irritation persists, consult a physician.  
Skin Contact: Prolonged contact may cause slight irritation of the skin. Wash with soap and water. If swallowed, consult a physician.  
Inhalation: If symptomatic, move to fresh air. Get medical attention if symptoms occur.

### REACTIVITY DATA

Conditions to Avoid: Excessive heat or cold  
Stability: Stable  
Incompatibility: None known  
Hazardous Decomposition Products: None known; Normal (CO<sub>2</sub>, CO)  
Hazardous Polymerization: Will not occur

### PRECAUTIONS FOR HANDLING AND USE

Pressurized containers may explode if heated. Ventilation: Local ventilation  
Protective Gloves: Recommended  
Eye Protection: Safety glasses  
Hygienic Practices: Wash with soap and water after exposure  
Respiratory Protection: Not required with adequate ventilation  
Other Protective Equipment: None  
Disposal: Empty aluminum cans should be relieved of pressure and recycled or disposed of in accordance with Federal, State and Local regulations.

### SPECIAL PRECAUTIONS/OTHER COMMENTS

Protect from sunlight and do not expose to temperatures exceeding 115° F (46° C). Store inside at a temperature of 65°–95° F. in a well-ventilated area. Do not allow product to freeze.

### PROPELLANT

1,1,1, 2 - tetrafluoroethane, UN 1950, aerosols, non-flammable, (each not to exceed 1L capacity), 2.2

### TRANSPORTATION DATA

D.O.T. Hazard Class: 2.2  
Consumer Commodity ORM-D

<b>HEALTH</b>	<b>1</b>
<b>FLAMMABILITY</b>	<b>0</b>
<b>REACTIVITY</b>	<b>0</b>
<b>PERSONAL PROTECTION</b>	<b>B</b>